



16K
HEAVY DUTY
SERIES

BUILT WITH TRUE 8K AXLES



GOOSENECK SYSTEM

Standard Features

Toolbox with Chain Rack

Chain Tray

Spare Tire

Spare Tire Mount

Front Bump Rail

Model	GVW	Usable Deck Size	Empty Weight
1620 GN DO HD	16,000	20' x 98.25"	Est. 3,530 lbs.
1626 GN DO HD	16,000	25'-4" x 98.25"	Est. 3,860 lbs.

STANDARD SPECIFICATIONS	1620 GN DO HD	1626 GN DO HD
Overall Width	102"	102"
Overall Length	28'	32'
Payload Capacity	12,540 lbs.	12,140 lbs.
Ramp Length	Approx. 4'	Approx. 4'
Tongue Length	96"	96"
Deck Height	35"	35"
Loading Angle	14°	14°
Overall Deck Length	20'	25'-4"
Dovetail Length	60"	60"
Wheel Size	16"	16"
Tires	ST235/80R16G - 14 ply	ST235/80R16G - 14 ply
Number of Lug Bolts	8 per wheel (32)	8 per wheel (32)
Axle	8K Fixed	8K Fixed
Suspension	Rubber Torsion	Rubber Torsion
Brakes	Electric Self-Adjusting	Electric Self-Adjusting
Coupler	2-5/16"	2-5/16"
Coupler Position	Adjustable	Adjustable
Jack Style	Dual 12K Jacks	Dual 12K Jacks
Jack Rating	12,000 lbs. each (24,000 lbs. total)	12,000 lbs. each (24,000 lbs. total)
Stake Pockets	12 per side (24 total)	14 per side (28 total)
Lighting	LED	LED