

# POWERHOUSE MODELS



## 16K SERIES



### GOOSENECK SYSTEM

#### Standard Features

Toolbox with Chain Rack

Chain Tray

Spare Tire

Spare Tire Mount

Front Bump Rail

| Model      | GVW    | Usable Deck Size | Empty Weight    |
|------------|--------|------------------|-----------------|
| 1620 GN DO | 16,000 | 20' x 98.25"     | Est. 3,460 lbs. |
| 1626 GN DO | 16,000 | 25'-4" x 98.25"  | Est. 3,780 lbs. |

| STANDARD SPECIFICATIONS | 1620 GN DO                              | 1626 GN DO                              |
|-------------------------|---|---|
| Overall Width           | 102"                                    | 102"                                    |
| Overall Length          | 28'                                     | 32'                                     |
| Payload Capacity        | 12,480 lbs.                             | 12,220 lbs.                             |
| Ramp Length             | Approx. 4'                              | Approx. 4'                              |
| Tongue Length           | 96"                                     | 96"                                     |
| Deck Height             | 35"                                     | 35"                                     |
| Loading Angle           | 14°                                     | 14°                                     |
| Overall Deck Length     | 20'                                     | 25'-4"                                  |
| Dovetail Length         | 60"                                     | 60"                                     |
| Wheel Size              | 16"                                     | 16"                                     |
| Tires                   | ST235/80R16G - 10 ply                   | ST235/80R16G - 10 ply                   |
| Number of Lug Bolts     | 8 per wheel (32)                        | 8 per wheel (32)                        |
| Axle                    | 7K Fixed                                | 7K Fixed                                |
| Suspension              | Rubber Torsion                          | Rubber Torsion                          |
| Brakes                  | Electric Self-Adjusting                 | Electric Self-Adjusting                 |
| Coupler                 | 2-5/16"                                 | 2-5/16"                                 |
| Coupler Position        | Adjustable                              | Adjustable                              |
| Jack Style              | Dual 12K Jacks                          | Dual 12K Jacks                          |
| Jack Rating             | 12,000 lbs. each<br>(24,000 lbs. total) | 12,000 lbs. each<br>(24,000 lbs. total) |
| Stake Pockets           | 12 per side (24 total)                  | 14 per side (28 total)                  |
| Lighting                | LED                                     | LED                                     |