

POWERHOUSE MODELS



Industry-Leading Standard Features

All-Aluminum Construction with No Structural Welds

Thunderstone Mesh Tarp

(4) Box Mounted D-Rings

Dual Function Rear Gate (Barn Door/Spreader Combo)

Large Capacity A-Frame Toolbox

Spare Tire & Mount

Rear Stabilizers

Tarp Tie-Downs

Safety Bar/Lock

Serviceable Box Floor

Available Accessories

1' Add-Ons for Additional Side Wall Height (3' and 4' Options)

Dimensional Lumber/Extrusion Holders for Top of Box

Hydraulic Jack (Easy Swap)

UHMW Liner

Solar Panel Charger

Additional Box Mounted D-Rings

Additional Removable Stake Pocket D-Rings

STANDARD SPECIFICATIONS

	1414 Dump	1416 Dump
GVWR	14,000 lbs.	14,000 lbs.
Empty Weight	Est. 3,460 lbs.	Est. 3,640 lbs.
Payload Capacity	10,540 lbs.	10,360 lbs.
Box Length	14'	16'
Box Inside Width	82"	82"
Overall Width	102"	102"
Box Floor Construction	Fully-Boxed Extrusion with 3/16" Top & 1/8" Bottom	Fully-Boxed Extrusion with 3/16" Top & 1/8" Bottom
Box Side Height	24"	24"
Hoist Type	Dexter Scissor	Dexter Scissor
Rear Gate	Barn door/Spreader Combo	Barn door/Spreader Combo
Tarp	Full-Length Mesh Tarp	Full-Length Mesh Tarp
Wheel Size	16"	16"
Tires	ST235/80R16 - 10 ply	ST235/80R16 - 10 ply
Number of Lug Bolts	8 per wheel (32)	8 per wheel (32)
Axle Rating	7K	7K
Suspension	Rubber Torsion	Rubber Torsion
Brakes	Electric Self-Adjusting	Electric Self-Adjusting
Coupler	2-5/16"	2-5/16"
Coupler Position	Adjustable	Adjustable
Jack Style	Jost Spring Extended Landing Leg	Jost Spring Extended Landing Leg
Jack Rating	12,000 lbs.	12,000 lbs.
Stake Pockets	4 per side (8 total)	4 per side (8 total)
Lighting	LED	LED